

BAR REINFORCEMENT

<u>DEPTH BELOW TOP OF GRADE</u>	<u>HORIZONTAL REINF.</u>	<u>VERTICAL REINF.</u>	<u>WALL THICKNESS</u>
0' TO 10'-0"	#4 @ 10" O.C.	#4 @ 18" O.C.	6"
10'-1" TO 15'-0"	#4 @ 8" O.C.	#4 @ 18" O.C.	6"
15'-1" TO 20'-0"	#4 @ 6" O.C.	#4 @ 18" O.C.	6"

REINFORCING SHOWN FOR PRECAST INLETS IS THE MINIMUM REQUIRED.  
ADDITIONAL REINFORCING FOR HANDLING IS THE RESPONSIBILITY OF  
THE CONTRACTOR.

WWF REINFORCEMENT

DEPTH BELOW  
TOP OF GRADE

- 0' TO 10'-0" WWF 3X6 W6 WIRES SPACED AT 3" TO RUN HORIZONTAL  
IN ALL CASES.
- 10'-1" TO 15'-0" WWF 3X6 W6 ADD #3 BAR @ 18" HORIZONTAL.
- 15'-1" TO 20'-0" WWF 3X6 W6 ADD #3 BAR @ 9" HORIZONTAL.  
OR ADD #4 BAR @ 15" HORIZONTAL.

Precast Concrete Sales Co.  
123 Route 303 Valley Cottage, N.Y. 10989  
Tel. (845) 268-4949 - Fax (845) 268-4376

CONT.  
JOB

N.J. CONCRETE INLETS REINF. SCHED.  
DATE DRAWN BY DRAWING NO.  
1/00 CLASSIC DESIGN 2-RS